

| | |
|-----------------------|--|
| Gauge | 12G、 14G、 7-14G |
| Knitting width | 36/52/72 inches |
| Knitting system | Single carriage with triple systems |
| Knitting speed | Max speed 1.7m/s;24 section programmable speed |
| Racking | Motor driven;max 2 inches |
| Needle actuator | 8 section of electronic needle selector |
| Sinker system | Crossed sinker,driven by stepping motor,could be adjustable according to different woven products,in order to reach various three-dimensional effect |
| Stitch density | 32 segments of electronic control,the use of subdivision technology,adjustable range:0-650 |
| Transfer | Both front and back,not affecting by the carriage direction |
| Roller device | High-order roller,make the cut-pieces more even and smooth |
| Motor connecting rod | Connecting rod driven by electron motor,make the direction changing more accurate |
| Adjustable tight tuck | Density of tight tuck is adjustable |
| Yarn conveyor | Conveyor yarn device or normal yarn storage setting,ensure the yarn conveyed timely |

| | |
|---------------------|--|
| Yarn feeder | The 2*8 yarn feeder group is arranged on the left and the right sides of the 4 double side guide rails. |
| Driving system | Belt drive,AC servo motor control |
| Date input | Through the U disk,computer connection for direct input of data. |
| Date input | Automatic stopping device if yarn broken,yarn knot,batching,striking,completion,overload,designated starting and stopping,program error happen |
| Protection device | Emergency stop device, cut off power supply unit, alarm indicator, cover for noise and dust protection (with parking sensor) |
| Control System | <p>1. Mai Hong control system</p> <p>2. the screen uses LCD touch display, graphical interface, system expansion memory up to 1G, can store a large number of pattern files, can be called at any time according to production needs</p> <p>3. Through the screen check, you can check the working status and actual position of the cam, and adjust it when the machine is running, which is the most convenient operation.</p> <p>4. the control system (software part) and the pattern making system are easy to upgrade, for free service 5 multi-language version switching (Chinese, English, Russian and other languages)</p> |
| Size and weight | L*W*H:2970x940x2010 mm; Net weight: 1145 kg |
| Power supply system | Voltage: AC 220V/380V;Frequency: 50HZ/60HZ;Power:2.0KW |